



DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)  
BOARD AND CODE ADMINISTRATION DIVISION

**MIAMI-DADE COUNTY  
PRODUCT CONTROL SECTION**

11805 SW 26 Street, Room 208  
Miami, Florida 33175-2474  
T (786) 315-2590 F (786) 315-2599

[www.miamidade.gov/economy](http://www.miamidade.gov/economy)

## NOTICE OF ACCEPTANCE (NOA)

**Soprema, Inc.**  
**310 Quadral Drive**  
**Wadsworth, OH. 44281**

### SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

### DESCRIPTION: Soprema Soprapap'r Self-Adhesive Air/Vapor Barrier

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 3.

The submitted documentation was reviewed by Alex Tigera.



**NOA No.: 14-0225.01**  
**Expiration Date: 12/18/19**  
**Approval Date: 12/18/14**  
**Page 1 of 3**

## ROOFING COMPONENT APPROVAL

**Category:** Roofing  
**Sub-Category:** Underlayment  
**Material:** SBS

### SCOPE:

This acceptance is for **Soprema Soprapap'r self-adhesive air/vapor barrier** as manufactured by Soprema Inc., as described in this Notice of Acceptance, for use with approved prepared roof assemblies as described in this Notice of Acceptance; designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone of the Florida Building Code.

### TRADE NAMES OF PRODUCTS MANUFACTURED OR LABELED BY APPLICANT:

<u>Product</u>	<u>Dimensions</u>	<u>Test Specification</u>	<u>Product Description</u>
Soprapap'r <i>Manufacturing Location #1</i>	45" x 133'	Various	A self-adhering air/vapor barrier membrane applied direct to deck for use in steel deck assemblies, composed of a SBS modified bitumen adhesive bottom layer and a tri-laminated woven polyethylene top layer.

### MANUFACTURING LOCATION:

1. Drummondville, Quebec (Canada)

### EVIDENCE SUBMITTED:

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
Trinity ERD	S45520.11.13-R2	Physical Properties	03/26/14

### APPROVED ASSEMBLIES:

**Deck Type 1:** Steel, Insulated or Non-insulated

**System Type:** Self-adhered sheet applied direct to deck. Mechanically attached overlaying insulation or roof cover.

**Air/Vapor Barrier:** Soprapap'r shall be installed with a minimum 3-inch side lap and a 6-inch end lap. Peel the release film back 3 ft and align the membrane to be parallel to the joints. Pull the release film under the membrane as the membrane is applied and secure into place using a heavy roller. Install subsequent rolls of the membrane in the same manner.

**Surfacing:** Approved Roof Assemblies over Steel Decking, See Limitation #3



NOA No.: 14-0225.01  
Expiration Date: 12/18/19  
Approval Date: 12/18/14  
Page 2 of 3

## **LABELING:**

All membranes or packaging shall bear the imprint or identifiable marking of the manufacturer's name or logo, city, state and the following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



## **BUILDING PERMIT REQUIREMENTS:**

Application for building permit shall be accompanied by copies of the following:

1. This Notice of Acceptance.
2. Any other documents required by the Building Official or applicable building code in order to properly evaluate the installation of this material.

## **GENERAL LIMITATIONS:**

1. Fire classification is not part of this acceptance.
2. This acceptance is for prepared roofing applications. Minimum deck requirements shall be in compliance with the applicable building code. Sopravap'r shall be installed in strict compliance with the applicable building code.
3. Sopravap'r is used as an air/vapor barrier in steel deck roofing assemblies utilizing mechanically fastened overlying components (insulations, coverboards and/or membranes). Steel deck roofing assemblies shall be listed under a current roof covering Notice of Acceptance.
4. Sopravap'r vapor barriers shall be applied to a smooth, clean and dry surface, free from irregularities. Substrate may be primed with an optional layer of Elastocol Stick prior to application if needed.
5. Sopravap'r shall not be left exposed as a temporary roof for longer than 30 days.
6. Sopravap'r shall not be applied over an existing roof membrane as a recover.

**END OF THIS ACCEPTANCE**



NOA No.: 14-0225.01  
Expiration Date: 12/18/19  
Approval Date: 12/18/14  
Page 3 of 3